

Printing date 05/24/2017 Reviewed on 05/24/2017

1 Identification

- . Product identifier
- . Trade name STEEL RACK ORANGE SM GL
- . Article number: 10098 . Manufacturer/Supplier: The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

Phone: 800-343-9353

Emergency Telephone number: 24/7 - 800-424-9300

2 Hazard(s) identification

. Classification of the substance or mixture



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Combustible Dust May form combustible dust concentrations in air.

- . Label elements
- . GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

— US —



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 1)

. Hazard pictograms







GHS05

GHS07

. Signal word Danger

. Hazard-determining components of labeling:

1, 3, 5-tris (oxiranylmethyl) -1, 3, 5-triazine-2, 4, 6(1H, 3H, 5H) -trione

. Hazard statements

Causes serious eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause damage to organs through prolonged or repeated exposure.

May form combustible dust concentrations in air.

. Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- . Classification system
- . NFPA ratings (scale 0-4)



Health = 2Fire = 1Reactivity = 1

HMIS-RATINGS (SCALE 0 - 4)



. Other hazards

Health = 2Fire = 1Reactivity = 1

- . Results of PBT and vPvB assessment
- . PBT: Not applicable. . vPvB: Not applicable.

3 Composition/information on ingredients

- . Chemical characterization: Mixtures
- . Description: Mixture consisting of the following components with harmless additives.

. Hazardous	Hazardous ingredients:			
7727-43-7	barium sulphate, natural	25-50%		
	(Cont.	d. on page 3)		



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

	. of page 2)
2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	2.5-10%
Acute Tox. 3, H301; Acute Tox. 3, H331; Muta. 1B, H340; STOT RE 2, H373; Eye Dam. 1, H318; Skin Sens. 1, H317	
1332-58-7 kaolin	< 2.5%

. Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- . Description of first aid measures
- . General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

. After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- . After skin contact Instantly wash with water and soap and rinse thoroughly.
- . After eye contact Rinse opened eye for several minutes under running water.
- . After swallowing Instantly call for doctor.
- . Information for doctor
- . Most important symptoms and effects, both acute and delayed

No further relevant information available.

. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- . Extinguishing media
- . Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

. Special hazards arising from the substance or mixture

No further relevant information available.

- . Advice for firefighters
- . Protective equipment: Put on breathing apparatus.

6 Accidental release measures

. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid causing dust.

- . Environmental precautions: Do not allow product to reach sewage system or water bodies.
- . Methods and material for containment and cleaning up:

Collect mechanically.

Ensure adequate ventilation.

. Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

. Protective Action Criteria for Chemicals

. PAC-1:				
7727-43-7 barium sulphate, natural		15 mg/m3		
471-34-1	calcium carbonate	45 mg/m3		
112926-00-8	Silicon dioxide	18 mg/m3		
	Pigment Black 11	21 mg/m3		
14808-60-7	quartz (SiO2)	0.075 mg/m3		
. PAC-2:				
7727-43-7	barium sulphate, natural	170 mg/m3		

(Contd. on page 4)



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 3)					
471-34-1	calcium carbonate	210 mg/m3			
112926-00-8	112926-00-8 Silicon dioxide				
1317-61-9	1317-61-9 Pigment Black 11				
14808-60-7	quartz (SiO2)	33 mg/m3			
. PAC-3:	. PAC-3:				
7727-43-7	barium sulphate, natural	990 mg/m3			
471-34-1	calcium carbonate	1,300 mg/m3			
112926-00-8	Silicon dioxide	1,200 mg/m3			
1317-61-9	Pigment Black 11	1,400 mg/m3			
14808-60-7	quartz (SiO2)	200 mg/m3			

7 Handling and storage

- . Handling
- . Precautions for safe handling

No special measures required.

Thorough dedusting.

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

. Information about protection against explosions and fires:





Keep ignition sources away - Do not smoke.

Keep breathing equipment ready.

Dust can combine with air to form an explosive mixture.

- . Conditions for safe storage, including any incompatibilities
- . Storage
- . Requirements to be met by storerooms and containers:

Store only in the original container.

Static charges may build up in the powder

- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep container tightly sealed.
- . Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- . Additional information about design of technical systems: No further data; see item 7.
- . Control parameters

. Components with critical values that require monitoring at the workplace:				
7727-43-7 bari	7727-43-7 barium sulphate, natural			
PEL (U.S.A)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction			
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction			
TLV (U.S.A)	Long-term value: 5* mg/m³ *inhalable fraction; E			
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction			
EV (Canada)	Long-term value: 10 mg/m³ total dust			
LMPE (Mexico)	Long-term value: 10 mg/m³			



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 4) 2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione Long-term value: 0.05 mg/m³ TLV (U.S.A) EL (Canada) Long-term value: 0.05 mg/m3 EV (Canada) Long-term value: 0.05 mg/m³ LMPE (Mexico) Long-term value: 0.05 mg/m³ 1332-58-7 kaolin PEL (U.S.A) Long-term value: 15* 5** mg/m³ *total dust **respirable fraction Long-term value: 10* 5** mg/m3 REL (U.S.A) *total dust **respirable fraction Long-term value: 2* mg/m³ TLV (U.S.A) E; as respirable fraction EL (Canada) Long-term value: 2 mg/m³ Long-term value: 2(D) mg/m³ EV (Canada) respirable

. Additional information:

The lists that were valid during the compilation were used as basis.

. Exposure controls

LMPE (Mexico)

•

- . Personal protective equipment
- . General protective and hygienic measures

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Store protective clothing separately.

Long-term value: 2* mg/m3

A4, *fracción respirable

. Breathing equipment:



In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

. Protection of hands:



Protective gloves.

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection:



Safety Glasses

. Body protection: Protective work clothing.



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 5)

9 Physical and Chemical Properties

. Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Solid

Colour: According to Trade Name

. Change in condition

Melting point/Melting range: > 50 C / 120F
Boiling point/Boiling range: Not applicable

Flash point: Not applicable

Inflammability (solid, gaseous) Not determined

. Ignition temperature:

Decomposition temperature: Not determined

. Self-inflammability: Product is not selfigniting.

. Danger of explosion: Product is not explosive. However,

formation of explosive air/dust mixtures is

possible

. Critical values for explosion:

Lower: Not determined.
Upper: Not determined.

Steam pressure: Not applicable.

. Density (Specific gravity) at 20 °C (68 °F) 1.6 g/cm³ (13.352 lbs/gal)

. Relative density
. Vapor density
. Evaporation rate
Not determined.
Not applicable.
Not applicable.

. Solubility in / Miscibility with

Water: Unsoluble

. Partition coefficient (n-octanol/water): Not determined.

. Viscosity:

dynamic: Not applicable.
kinematic: Not applicable.

. Solvent content:

Organic solvents: 0.0 %

Solids content: 100.0 %

. Other information No further relevant information available.

10 Stability and Reactivity

- . Reactivity No further relevant information available.
- . Chemical stability
- . Conditions to be avoided: No decomposition if used according to specifications.
- . Possibility of hazardous reactions No dangerous reactions known
- . Conditions to avoid No further relevant information available.
- . Incompatible materials: No further relevant information available.
- . Hazardous decomposition products: In case of fire: CO, CO2, NOx

(Contd. on page 7)



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 6)

11 Toxicological Information

- . Information on toxicological effects
- . Acute toxicity:

. LD/LC50 values that are relevant for classification:			
2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione			
Oral	LD50	188-1450 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	0.309-0.650 mg/l (rat)	

- . Primary irritant effect:
- . on the skin: No irritant effect.
- . on the eye: No irritant effect.
- . Sensitization: Sensitization possible by skin contact.
- . Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant

Harmful

The product can cause inheritable damage.

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)				
112926-00-8	Silicon dioxide	3		
14808-60-7	quartz (SiO2)	1		
. NTP (National Toxicology Program)				
14808-60-7 quartz (SiO2) K				
. OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

12 Ecological information

- . Toxicity
- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behaviour in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- . Additional ecological information:
- . General notes:

Water danger class 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.
- . Other adverse effects No further relevant information available.

13 Disposal considerations

- . Waste treatment methods
- . Recommendation





Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 7)

. Uncleaned packagings:

. Recommendation: Disposal must be made according to official regulations.

14 Transport information

. UN-Number n/a
. UN proper shipping name n/a

. Transport hazard class(es)

. DOT, IMDG, IATA

. Class Not regulated.

. Packing group n/a

. Environmental hazards:

. Marine pollutant: $N \circ$

. Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- . Safety, health and environmental regulations/legislation specific for the substance or mixture
- . SARA (Superfund Amendments and Reauthorization Act):

. Section 355	(Extremly hazardous substances):				
None of the	None of the ingredients is listed.				
. Section 313	. Section 313 (Specific toxic chemical listings):				
7727-43-7	barium sulphate, natural				
68186-90-3	chrome antimony titanium buff rutile				
. TSCA (Toxio	. TSCA (Toxic Substances Control Act):				
All ingredients are listed.					

. Proposition 65:

	. Ch	nemicals known to cause cancer:	
	No	one of the ingredients is listed.	
Γ	. Chemicals known to cause reproductive toxicity for females:		
	No	one of the ingredients is listed.	
Γ	. Chemicals known to cause reproductive toxicity for males:		
	No	one of the ingredients is listed.	

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

. Cancerogenity categories

. EPA (Environmental Protection Agency)					
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(or	al)		
. TLV (Thresh	. TLV (Threshold Limit Value established by ACGIH)				
1332-58-7	kaolin		A4		
14808-60-7	quartz (SiO2)		A2		
. NIOSH-Ca (National Institute for Occupational Safety and Health)					
14808-60-7	quartz (SiO2)				

. GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

(Contd. of page 8)

. Hazard pictograms







GHS05

GHS07

. Signal word Danger

. Hazard-determining components of labeling:

1, 3, 5-tris (oxiranylmethyl) -1, 3, 5-triazine-2, 4, 6(1H, 3H, 5H) -trione

. Hazard statements

Causes serious eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause damage to organs through prolonged or repeated exposure.

May form combustible dust concentrations in air.

. Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Contaminated work clothing must not be allowed out of the workplace.

 ${\it Wear protective gloves/protective clothing/eye protection/face protection.}$

IF ON SKIN: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER/doctor.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H301 Toxic if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H340 May cause genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

. Date of preparation / last revision 05/24/2017 / -

. Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 10)



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name STEEL RACK ORANGE SM GL

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 3: Acute toxicity - Category 3
Eye Dam. 1: Serious eye damage/eye irritation - Category 1
Skin Sens. 1: Skin sensitisation - Category 1
Muta. 1B: Germ cell mutagenicity - Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

. * Data compared to the previous version altered.

___ US ____