

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

## 1 Identification

- **Product identifier**
- **Trade name:** EW-10109Z AlumaBlast
- **Article number:** EW10109Z
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 Eastwood Products  
 263 Shoemaker Road  
 Pottstown, PA 19464  
 United States of America
- **Information department:** (610)705-5463
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222      Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas      H280      Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B      H340      May cause genetic defects.

Carc. 1B      H350      May cause cancer.

Repr. 2      H361      Suspected of damaging fertility or the unborn child.

STOT RE 2      H373      May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1      H304      May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.

Eye Irrit. 2A      H319      Causes serious eye irritation.

Skin Sens. 1      H317      May cause an allergic skin reaction.

STOT SE 3      H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: **EW-10109Z AlumaBlast**

(Contd. of page 1)

· **Hazard pictograms**

GHS02   GHS04   GHS07   GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

toluene  
Stoddard solvent  
acetone  
Alkyd Resin  
2-butanone oxime

· **Hazard statements**

H222      *Extremely flammable aerosol.*  
H280      *Contains gas under pressure; may explode if heated.*  
H315      *Causes skin irritation.*  
H319      *Causes serious eye irritation.*  
H317      *May cause an allergic skin reaction.*  
H340      *May cause genetic defects.*  
H350      *May cause cancer.*  
H361      *Suspected of damaging fertility or the unborn child.*  
H335-H336 *May cause respiratory irritation. May cause drowsiness or dizziness.*  
H373      *May cause damage to organs through prolonged or repeated exposure.*  
H304      *May be fatal if swallowed and enters airways.*

· **Precautionary statements**

P210      *Keep away from heat/sparks/open flames/hot surfaces. No smoking.*  
P251      *Do not pierce or burn, even after use.*  
P260      *Do not breathe dust/fume/gas/mist/vapors/spray.*  
P211      *Do not spray on an open flame or other ignition source.*  
P280      *Wear protective gloves/protective clothing/eye protection/face protection.*  
P264      *Wash thoroughly after handling.*  
P271      *Use only outdoors or in a well-ventilated area.*  
P272      *Contaminated work clothing must not be allowed out of the workplace.*  
P201      *Obtain special instructions before use.*  
P202      *Do not handle until all safety precautions have been read and understood.*  
P301+P310 *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*  
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
  
P321      *Specific treatment (see on this label).*  
P304+P340 *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
P312      *Call a POISON CENTER/doctor if you feel unwell.*  
P363      *Wash contaminated clothing before reuse.*  
P308+P313 *IF exposed or concerned: Get medical advice/attention.*  
P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*  
P337+P313 *If eye irritation persists: Get medical advice/attention.*  
P314      *Get medical advice/attention if you feel unwell.*  
P331      *Do NOT induce vomiting.*  
P302+P352 *IF ON SKIN: Wash with plenty of water.*  
P362+P364 *Take off contaminated clothing and wash it before reuse.*  
P405      *Store locked up.*

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: **EW-10109Z AlumaBlast**

(Contd. of page 2)

P410+P403 *Protect from sunlight. Store in a well-ventilated place.*  
 P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*  
 P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*  
 P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**

Health = \*1

Fire = 4

Reactivity = 3

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

74-98-6	propane	13 - 30%
108-88-3	toluene	13 - 30%
67-64-1	acetone	13 - 30%
	Alkyd Resin	13 - 30%
123-86-4	n-butyl acetate	7 - 10%
107-87-9	pentan-2-one	5 - 7%
7429-90-5	aluminium	1.5 - 5%
763-69-9	ethyl 3-ethoxypropionate	1.5 - 5%
14807-96-6	Talc	1.5 - 5%
112926-00-8	precipitated Silica (Silica-Amorphous)	1-1.5%
108-10-1	4-methylpentan-2-one	≤1%
8052-41-3	Stoddard solvent	≤1%
96-29-7	2-butanone oxime	≤1%

USA

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 3)

## 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

74-98-6	propane	5500* ppm
108-88-3	toluene	67 ppm
67-64-1	acetone	200 ppm
123-86-4	n-butyl acetate	5 ppm
107-87-9	pentan-2-one	150 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
78-93-3	butanone	200 ppm
108-10-1	4-methylpentan-2-one	75 ppm

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

**Trade name: EW-10109Z AlumaBlast**

(Contd. of page 4)

8052-41-3	Stoddard solvent	300 mg/m <sup>3</sup>
96-29-7	2-butanone oxime	30 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	60 ppm
1330-20-7	xylene	130 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	3.4 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>

**· PAC-2:**

74-98-6	propane	17000** ppm
108-88-3	toluene	560 ppm
67-64-1	acetone	3200* ppm
123-86-4	n-butyl acetate	200 ppm
107-87-9	pentan-2-one	830 ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
78-93-3	butanone	2700* ppm
108-10-1	4-methylpentan-2-one	500 ppm
8052-41-3	Stoddard solvent	1,800 mg/m <sup>3</sup>
96-29-7	2-butanone oxime	56 ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	120 ppm
1330-20-7	xylene	920* ppm
111-77-3	2-(2-methoxyethoxy)ethanol	37 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
7447-41-8	lithium chloride	25 mg/m <sup>3</sup>

**· PAC-3:**

74-98-6	propane	33000*** ppm
108-88-3	toluene	3700* ppm
67-64-1	acetone	5700* ppm
123-86-4	n-butyl acetate	3000* ppm
107-87-9	pentan-2-one	5000* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
78-93-3	butanone	4000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
8052-41-3	Stoddard solvent	29500** mg/m <sup>3</sup>

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 5)

96-29-7	2-butanone oxime	250 ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
111-76-2	2-butoxyethanol	700 ppm
1330-20-7	xylene	2500* ppm
111-77-3	2-(2-methoxyethoxy)ethanol	220 ppm
107-98-2	1-methoxy-2-propanol	660 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 74-98-6 propane

PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; NIC-EX

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 6)

**108-88-3 toluene**

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

**67-64-1 acetone**

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm BEI

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**107-87-9 pentan-2-one**

PEL	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

**112926-00-8 precipitated Silica (Silica-Amorphous)**

PEL	20mppcf or 80mg/m <sup>3</sup> %SiO <sub>2</sub>
REL	Long-term value: 6 mg/m <sup>3</sup> See Pocket Guide App. C
TLV	TLV withdrawn

**108-10-1 4-methylpentan-2-one**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI

**8052-41-3 Stoddard solvent**

PEL	Long-term value: 2900 mg/m <sup>3</sup> , 500 ppm
REL	Long-term value: 350 mg/m <sup>3</sup> Ceiling limit value: 1800* mg/m <sup>3</sup> *15-min
TLV	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 7)

**96-29-7 2-butanone oxime**

WEEL	Long-term value: 10 ppm
DSEN	

**· Ingredients with biological limit values:****108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
-----	---

	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
--	--

	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
--	--

**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**108-10-1 4-methylpentan-2-one**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

(Contd. on page 9)

USA



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 8)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Aerosol  
**Color:** According to product specification

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** -44 °C

- **Flash point:** -97 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

- **Explosion limits:**

**Lower:** 1.2 Vol %  
**Upper:** 13.0 Vol %

- **Vapor pressure at 20 °C:** 8300 hPa

- **Density at 20 °C:** 0.79366 g/cm<sup>3</sup>

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

(Contd. on page 10)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 9)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 77.2 %
  - VOC content:** 61.3 %
  - 509.3 g/l / 4.25 lb/gl
- **Solids content:** 22.5 %
- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
14807-96-6	Talc	3
108-10-1	4-methylpentan-2-one	2B
	BENTONITE	suspected carcinogen <2% 14808-60-7

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 10)

1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

(Contd. on page 12)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 11)

· **Transport hazard class(es)**· **DOT**

· **Class** 2.1  
 · **Label** 2.1

· **ADR**

· **Class** 2 5F Gases  
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1  
 · **Label** 2.1

· **Packing group**· **DOT, ADR, IMDG, IATA** Void· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user**

Warning: Gases

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:  
 Category A. For AEROSOLS with a capacity above 1 litre:  
 Category B. For WASTE AEROSOLS: Category C, Clear of living  
 quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except for  
 division 1.4. For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2. For  
 WASTE AEROSOLS: Segregation as for the appropriate subdivision  
 of class 2.

· **Transport in bulk according to Annex II of  
 MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 13)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 12)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **ADR**

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
7429-90-5	aluminium
14807-96-6	Talc
78-93-3	butanone
108-10-1	4-methylpentan-2-one
	COBALT CARBOXYLATE
	Acrylic Resin
111-76-2	2-butoxyethanol
1330-20-7	xylene
111-77-3	2-(2-methoxyethoxy)ethanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

74-98-6	propane
108-88-3	toluene
67-64-1	acetone
123-86-4	n-butyl acetate
107-87-9	pentan-2-one
7429-90-5	aluminium
763-69-9	ethyl 3-ethoxypropionate
14807-96-6	Talc
78-93-3	butanone

(Contd. on page 14)

USA

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: **EW-10109Z AlumaBlast**

(Contd. of page 13)

108-10-1	4-methylpentan-2-one
8052-41-3	Stoddard solvent
96-29-7	2-butanone oxime
64742-88-7	Solvent naphtha (petroleum), medium aliph.
1333-86-4	Carbon black
111-76-2	2-butoxyethanol
1330-20-7	xylene
111-77-3	2-(2-methoxyethoxy)ethanol
5567-15-7	Novaperm yellow HR02
107-98-2	1-methoxy-2-propanol
149-57-5	2-ethylhexanoic acid
100-41-4	ethylbenzene
7447-41-8	lithium chloride
61791-55-7	Amines, N-tallow alkyltrimethylenedi-

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
108-10-1	4-methylpentan-2-one

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
67-64-1	acetone	I
78-93-3	butanone	I
108-10-1	4-methylpentan-2-one	I
111-76-2	2-butoxyethanol	NL
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
67-64-1	acetone	A4
7429-90-5	aluminium	A4
14807-96-6	Talc	A4

(Contd. on page 15)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: **EW-10109Z AlumaBlast**

(Contd. of page 14)

1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS04   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*toluene*

*Stoddard solvent*

*acetone*

*Alkyd Resin*

*2-butanone oxime*

· **Hazard statements**

H222      *Extremely flammable aerosol.*

H280      *Contains gas under pressure; may explode if heated.*

H315      *Causes skin irritation.*

H319      *Causes serious eye irritation.*

H317      *May cause an allergic skin reaction.*

H340      *May cause genetic defects.*

H350      *May cause cancer.*

H361      *Suspected of damaging fertility or the unborn child.*

H335-H336      *May cause respiratory irritation. May cause drowsiness or dizziness.*

H373      *May cause damage to organs through prolonged or repeated exposure.*

H304      *May be fatal if swallowed and enters airways.*

· **Precautionary statements**

P210      *Keep away from heat/sparks/open flames/hot surfaces. No smoking.*

P251      *Do not pierce or burn, even after use.*

P260      *Do not breathe dust/fume/gas/mist/vapors/spray.*

P211      *Do not spray on an open flame or other ignition source.*

P280      *Wear protective gloves/protective clothing/eye protection/face protection.*

P264      *Wash thoroughly after handling.*

P271      *Use only outdoors or in a well-ventilated area.*

P272      *Contaminated work clothing must not be allowed out of the workplace.*

P201      *Obtain special instructions before use.*

P202      *Do not handle until all safety precautions have been read and understood.*

P301+P310      *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*

P305+P351+P338      *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P321      *Specific treatment (see on this label).*

P304+P340      *IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

P312      *Call a POISON CENTER/doctor if you feel unwell.*

(Contd. on page 16)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW-10109Z AlumaBlast

(Contd. of page 15)

P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Date of preparation / last revision** 04/11/2017 / 8

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

(Contd. on page 17)

USA



**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 04/11/2017

Reviewed on 04/11/2017

**Trade name: EW-10109Z AlumaBlast**

(Contd. of page 16)

*Press. Gas: Gases under pressure – Compressed gas*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Muta. 1B: Germ cell mutagenicity – Category 1B*  
*Carc. 1B: Carcinogenicity – Category 1B*  
*Repr. 2: Reproductive toxicity – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*  
*Asp. Tox. 1: Aspiration hazard – Category 1*

· **\* Data compared to the previous version altered.**

USA