

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 10285
Product Name: HotCoat Powder Reflective Chrome
Product Use: Powder paint
Print date: 07/Dec/2010
Revision Date: 07/Dec/2010

Manufactured For

The Easthill Group
dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200

24-Hour Medical Emergency Phone: Chem-Trec 800-424-9300

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

- Moderate eye irritation

Skin Contact:

- Causes mild skin irritation.
- May cause sensitization by skin contact.

Ingestion:

- Harmful if swallowed.

Inhalation:

- May cause irritation of respiratory tract.
- Harmful by inhalation.

This product contains ingredients that may contribute to the following potential chronic health effects:

- Possible sensitization.

Teratogens:

- Contains material that may cause adverse reproductive effects.
- Male reproductive toxin

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
TGIC 2451-62-9	5 - 10	1,3,5-TRIAZINE-2,4,6(1H, 3H,5H)-TRIONE,1,3,5-TRIS(OXIRANYLMETHYL)-
ALUMINUM 7429-90-5	1 - 5	Aluminum

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart. Do not rub eye.

Skin Contact:

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

Ingestion:

Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention.

Inhalation:

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit):	950
Flash point (Celsius):	510
Lower explosive limit (%):	not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

Unusual fire and explosion hazards:

Refer to 1995 edition of NFPA 33 Appendix A. A minimum explosive concentration of dust in the air of 30 grams per cubic meter of air can be used. Dust control and good housekeeping are required. Dust may also carry a static charge. Make sure equipment and personnel are grounded to avoid static discharge.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Decomposes without flashing

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Minimize the free fall distance of powder when loading, unloading or conveying to avoid dust generation and potential static discharge. Keep container closed when not in use. Keep away from heat, sparks and open flame. - No smoking. To prevent caking of product, do not store above 80 degree F. (27 degree C.).

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Safety glasses (with side shields) Wear safety glasses or goggles to protect against exposure.

Skin protection:

Gloves: Neoprene or other nonporous.

Other Personal Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas. Chemical resistant apron

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with a particulate filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment. Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
ALUMINUM 7429-90-5	1 - 5	15 mg/m ³ TWA dust total 5 mg/m ³ TWA respirable fraction		

ACGIH Threshold Limit Value (TLV's)

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
TGIC 2451-62-9	5 - 10	0.05 mg/m ³ TWA			
ALUMINUM 7429-90-5	1 - 5	1 mg/m ³ TWA respirable fraction			

9. PHYSICAL PROPERTIES

Odor:	Powder with no distinct odor.
Physical State:	powder
pH:	not determined
Vapor pressure:	not determined mmHg @ 68°F (20°C)
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	10.27
Specific Gravity:	1.23
Evaporation rate (butyl acetate = 1.0):	not determined
Flash point (Fahrenheit):	950
Flash point (Celsius):	510
Lower explosive limit (%):	not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Incompatibility:	None known.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Nitrogen compounds.

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
TGIC 2451-62-9	5 - 10	= 188 mg/kg Oral LD50 Rat

Mutagens/Teratogens/Carcinogens:

Possible mutagen

Contains triglycidyl isocyanurate (TGIC) which has been shown to cause genetic damage, chromosomal aberration and death in reproductive cells in laboratory animals.

FOR COATINGS CONTAINING 4% TO 6% TGIC, OUR SUPPLIER OF TGIC REPORTS AN 8 HOUR TWA EXPOSURE LIMIT OF 1 MG/CU M OF AIR IS APPROPRIATE. TRIGLYCIDYL ISOCYANURATE (TGIC) HAS BEEN SHOWN IN LABORATORY TESTING TO CAUSE MUTAGENIC AND TOXIC REPRODUCTIVE SYSTEM EFFECTS IN MALE MICE WHO INHALE OR INGEST TGIC. IN THESE STUDIES, MALE MICE WHO INHALED TGIC DOSES EXCEEDING 2.5 MG/CU M FOR 6 HOURS/DAY FOR 5 DAYS SHOWED EVIDENCE OF GENETIC DAMAGE, CHROMOSOMAL ABERRATION AND DEATH OF REPRODUCTIVE CELLS. MUTAGENIC EFFECTS WERE ALSO OBSERVED IN CHINESE HAMSTERS (IN VIVO). BASED ON THESE RESULTS, THE MANUFACTURER OF TGIC RECOMMENDS THAT THE PERMISSIBLE INTERNAL EXPOSURE LIMIT OF 0.025 MG/CU M SHOULD BE USED FOR PROTECTION OF WORKERS USING OR BEING EXPOSED TO TGIC (ON A PURE TGIC BASIS).

Contains material that may cause adverse reproductive effects. Male reproductive toxin

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Developmental Toxicity	California Prop 65 - Reproductive (Male)
TGIC 2451-62-9	5 - 10		Listed. Initial date 8/1/09 - male reproductive toxicity

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

UN ID Number (msds): NRPDRY
Proper Shipping Name: PAINT, DRY, NOT REGULATED

U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

UN ID Number (msds): NRPDRY
Proper Shipping Name: PAINT, DRY, NOT REGULATED

International Maritime Organization (IMO):

IMO UN/ID Number (msds): NRPDRY
Proper Shipping Name: PAINT, DRY, NOT REGULATED

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
ALUMINUM 7429-90-5	1 - 5		Form R reporting required for 1.0 % de minimis concentration	

SARA 311/312 Hazard Class:

Acute: yes
Chronic: yes
Flammability: no
Reactivity: no
Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

Pennsylvania Right To Know:

TGIC	2451-62-9
ALUMINUM	7429-90-5

Additional Non-Hazardous Materials

PROPRIETARY RESIN	Trade Secret
-------------------	--------------

California Proposition 65:

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories**US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION**HMIS Codes**

Health:	2*
Flammability:	1
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pinsky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

Prepared By:	Regulatory Affairs Department
Print date:	07/Dec/2010
Revision Date:	07/Dec/2010