#### MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> Trizact<sup>TM</sup> Abrasives Product, 307EA A6-A100 05/19/10

Distributed By:

The Easthill Group dba/ The Eastwood Company

263 Shoemaker Road Pottstown, PA 19464

USA & Canada: 800-345-1178; Outside USA: 610-323-2200 **Emergency Contact: Chem-Trec 800-424-9300** 

**Material Safety Data Sheet** 

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

3M<sup>TM</sup> Trizact<sup>TM</sup> Abrasives Product, 307EA A6-A100 PRODUCT NAME:

**MANUFACTURER:** 

**DIVISION:** 

**Abrasives Systems Division** 

ADDRESS:

3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 

05/19/10

**Supercedes Date:** 

10/30/08

**Document Group:** 23-1899-6

**Product Use:** 

Intended Use:

Abrasive Product

## **SECTION 2: INGREDIENTS**

Ingredient	<u>C.A.S. No.</u>	% by Wt 20 - 45	
Aluminum Oxide Mineral	1344-28-1		
Inorganic Fluoride	14075-53-7	5 - 20 .2 - 1.75 20 - 40	
Additive	13463-67-7		
Cured Resin	Mixture		
Cotton Backing	Mixture	20 - 35	

## SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Solid abrasive product

General Physical Form: Solid

Immediate health, physical, and environmental hazards:

May cause target organ effects. This document covers

only the 3M product. For complete assessment, when determining the degree of hazard, the material being abraded must also be

considered.

## 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

#### Inhalation:

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

May be absorbed following inhalation and cause target organ effects.

#### Ingestion:

No health effects are expected.

#### **Target Organ Effects:**

Prolonged or repeated exposure may cause:

Hard Tissue Effects: Signs/symptoms may include color changes in the teeth and nails; changes in development of bone, teeth or nails; weakening of the bones; and/or hair loss.

## **SECTION 4: FIRST AID MEASURES**

#### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention. No need for first aid is anticipated.

### **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature** 

Not Applicable

Flash Point

Not Applicable

Flammable Limits - LEL

Not Applicable

Flammable Limits - UEL

Not Applicable

#### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable. None inherent in this product.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** 

Not applicable.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1 HANDLING

For industrial or professional use only. Avoid breathing of dust created by sanding, grinding or machining. Avoid eye contact with dust or airborne particles. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Sparks and particles flying from the product during sanding or grinding can cause injury and fire.

#### 7.2 STORAGE

Store in a cool, dry place.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation for sanding, grinding or machining. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

## 8.2.1 Eye/Face Protection

Avoid eye contact. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations.

The following eye protection(s) are recommended: Safety Glasses with side shields

#### 8.2.2 Skin Protection

Avoid skin contact. Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

#### 8.2.3 Respiratory Protection

Avoid breathing of dust created by sanding, grinding or machining. Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate resipratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with N95 particulate filters

. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Not an expected route of exposure. Wash hands after handling and before eating.

#### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<b>Authority</b>	<b>Type</b>	Limit	<b>Additional Information</b>
Aluminum Oxide Mineral	CMRG	TWA	1 fiber/cc	
Aluminum Oxide Mineral	OSHA	TWA, respirable	5 mg/m3	
		fraction	J	
Aluminum Oxide Mineral	OSHA	TWA, as total dust	15 mg/m3	
Additive	ACGIH	TWA	10 mg/m3	
Additive	CMRG	TWA, as respirable	5 mg/m3	
		dust		
Additive	OSHA	TWA, as total dust	15 mg/m3	

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Odor, Color, Grade: Solid abrasive product

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableBoiling pointNot Applicable

Vapor Density Not Applicable

Vapor Pressure Not Applicable

Specific GravityNot ApplicablepHNot ApplicableMelting pointNot ApplicableSolubility In WaterNot Applicable

**Evaporation rate**Kow - Oct/Water partition coef
Not Applicable
Not Applicable

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionHydrogen FluorideDuring Combustion

**Hazardous Decomposition:** Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### MATERIAL SAFETY DATA SHEET 3MTM TrizactTM Abrasives Product, 307EA A6-A100 05/19/10

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **ECOTOXICOLOGICAL INFORMATION**

Not determined.

#### CHEMICAL FATE INFORMATION

Not determined.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: The substrate that was abraded must be considered as a factor in the disposal method for this product. Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste. Combustion products will include HF. Facility must be capable of handling halogenated materials.

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

### **SECTION 15: REGULATORY INFORMATION**

### US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

## MATERIAL SAFETY DATA SHEET 3M<sup>TM</sup> Trizact<sup>TM</sup> Abrasives Product, 307EA A6-A100 05/19/10

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

#### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

#### INTERNATIONAL REGULATIONS

Contact 3M for more information.

WHMIS: Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:** 

Section 1: Product name was modified.

Copyright was modified.

Section 8: Skin protection phrase was modified.

Section 8: Eye/face protection information was modified.

Section 8: Respiratory protection - recommended respirators information was modified.

Section 14: Transportation legal text was modified.

Page Heading: Product name was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

#### MATERIAL SAFETY DATA SHEET 3MTM TrizactTM Abrasives Product, 307EA A6-A100 05/19/10

Section 9: Property description for optional properties was added.

Section 10.1 Conditions to avoid heading was added.

Section 10.2 Materials to avoid heading was added.

Section 6: Environmental procedures information was added.

Section 10: Materials to avoid physical property was added.

Section 10: Conditions to avoid physical property was added.

Section 8: Hand protection information was added.

Section 6: Release measures information was deleted.

Section 10: Materials and conditions to avoid physical property was deleted.

Section 8: Exposure guidelines legend was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com