



DO THE JOB RIGHT.

SAFETY DATA SHEET

SECTION 1 / Identification

IDENTITY: PREMIUM BUFFING COMPOUND
PRODUCT CODE: 13132A - 13194A GREASELESS

Manufacturer/Distributor: Eastwood Company
Address: 263 Shoemaker Road
Pottstown, PA 19464
Telephone No: 800-343-9353
Emergency Telephone No: 800-424-9300
Date: Chemtrec
6/1/2015

SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.
Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

Signal Word:
Warning



SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Metal Oxides	1309-37-1	less than 15 %
Silica Abrasive	1317-65-3	less than 30%
Aluminum Oxide	1344-28-1	less than 70%
Hyde Glue	9000-70-0	less than 10%

SECTION 4: First Aid Measures

Ingestion: If swallowed - seek medical attention
Inhalation: Move to a fresh air environment
Eye Contact: Flush thoroughly with water and call physician
Skin Contact: Remove dust from skin with warm water and soap

SECTION 5: Firefighting measures

Flash Point (method used): 350° F (CoC)
LEL: N/A
Extinguishing Media: CO₂ Dry Chemical
Special Fire Fighting Instructions: Use Air Pack - Treat as Grease Fire
Unusual Fire and Explosion Haz: Dense smoke
Flammable Limits: No Data
UEL: N/A

SECTION 6: Accidental release measures

If material is spilled or released - sweep up with broom and dispose. Follow normal clean up procedures per State and local laws - Care taken to prevent dust from becoming airborne.

SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in a cool dry area
 No other precautions apply

SECTION 8: Exposure controls/personal protection

Hazardous Guidelines:

Hazardous Component	OSHA PEL	ACGIH / TLV
Metal Oxides	5 mg ./m ³	5 mg ./m ³
Silica Abrasive	.1 mg ./m ³	.1 mg ./m ³
Aluminum Oxide	15 mg ./m ³	10 mg ./m ³
Hyde Glue	N/A	N/A

Special: None

Mechanical (General): To maintain employee below permissible limits.

Respiratory Protection: OSHA/MOHA approved dust mask / respirator

Gloves: Yes

Eye Protection: Safety Glasses

Other: Long sleeve protective clothing

SECTION 9: Physical and chemical properties

Boiling Point: > 450°F
Vapor Pressure (mm Hg): N/A
Vapor Density: N/A
Solubility in Water: Insoluble
Appearance & Odor: Red ,Green, Brown, Blue, Orange-packed in plastic bag / low odor

Specific Gravity: 1.9 to 2.6
Melting Point: 130°F
Evaporation Rate: N/A
(Butyl Acetate=1)

SECTION 10: Stability and Reactivity

Stability: Yes
Incompatibility: N/A
Hazardous Decomposition of By-Products: N/A
Hazardous Polymerization: Will not occur
Conditions to Avoid: N/A

SECTION 11: Toxicological Information

Route(s) of Entry : **Inhalation:** Yes **Skin:** No **Ingestion:** No

Health Hazards (Acute and Chronic): Coughing and sneezing. Buffing operations may cause lint and abrasives to become airborne. Respirator and ventilation is recommended.

Effects of overexposure: N/A
Carcinogenicity: N/A **NTP:** N/A
IARC Monographs: No **OSHA Regulated:** No

SECTION 12: Ecological information (Non-Mandatory)

ECOTICITY : None

SECTION 13: Disposal considerations (Non-Mandatory)

Per State and Local Law

SECTION 14: Transport Information (Non-Mandatory)

Not regulated as dangerous goods

SECTION 15: Regulatory Information (Non-Mandatory)

None

SECTION 16: Other Information (Non-Mandatory)

Revision Date: 05/12/2017

Revision Summary:

Update all sections per GHS compliance

Revised by: A. Battle

