



DO THE JOB RIGHT.

DATE ISSUED:	2/05/2018
Version No.:	50200211-5

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Eastwood Single Stage Urethane 2.8 VOC Automotive Paint

PRODUCT CODE: See list below

PRODUCT USE: FOR PROFESSIONAL USE ONLY

MANUFACTURED FOR:

The Easthill Group
dba The Eastwood Company
263 Shoemaker Road,
Pottstown, PA 19464
USA: 1-800-345-1178 or (610) 323-2200 CANADA: 1-800-820-9042

24 HR. EMERGENCY TELEPHONE NUMBER:

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure
Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

13703ZP	Rat Rod Silver Metallic Matte Finish	50213ZP	Reptile Red	50275ZP	Regal Red (Chevy)
13724ZP	Jade Green Metallic	50214ZP	Burnout Blue Metallic	50276ZP	Wimbledon White (Ford)
13727ZP	Brown Sugar Metallic	50215ZP	Electric Yellow	50277ZP	Candy Apple Red (Ford)
13729ZP	Gold Digger Metallic	50216ZP	Quarter Mile Candy Red	50280ZP	Bonneville Black Cherry Pearl
14880ZPA	Carbon Metallic	50217ZP	Pinup Red	50281ZP	Bright Aqua Pearl
15701ZPA	Platinum Frost Silver Metallic	50218ZP	Prostreet Red	50282ZP	Midnight Metallic
15702ZPA	Redline Red	50219ZP	Eastwood Blue Pearl	50283ZP	Meteor Metallic Gray
15703ZPA	Tropical Sunset Orange Pearl	50220ZP	Cruise Night Blue Metallic	50284ZP	Pearl Necklace White
15704ZPA	Deep Lagoon Blue	50221ZP	Gasser Green Metallic	50285ZP	Coastal Highway Blue
15705ZPA	Destroyer Gray	50223ZP	USA Bright White	50286ZP	Canyon Dusk Copper
15706ZPA	Sub Zero Blue Pearl	50224ZP	Tunnel Ram Metallic Gray	50287ZP	Molten Red Metallic
15707ZPA	Fireball Red Pearl	50225ZP	Malibu Sunset Metallic Orange	50288ZP	Moonlight Drive Metallic
15708ZPA	Agave Green Metallic	50227ZP	Beach Bum Aqua Metallic	51004ZP	Boulevard Black
15709ZPA	Sandstone Tan	50228ZP	Royal Blue	51073ZP	Rat Rod Gray
16100ZP	Battlefield Olive Drab	50229ZP	Hugger Orange	51074ZP	Rat Rod Red
16102ZP	Lead Sled Metallic	50230ZP	Plum Loco	51075ZPA	Dead Rat Flat Black
16103ZP	9mm Metallic	50231ZP	Champagne Metallic	51076ZPA	Dead Rat Flat Black
16104ZP	Caribbean Bay Blue Pearl	50232ZP	Euro Racing Green	51457ZP	Rat Rod Satin Black
16107ZP	Black Ice Silver Metallic	50253ZP	2K Underhood Black Urethane	51678ZPA	Silver Metallic Candeez Base
16111ZP	Black Ice Gold Pearl	50254ZP	USA Urethane White	51685ZPA	Mayan Gold Metallic Candeez Base
16112ZP	Afterburner Red	50266ZP	Mulsanne Blue Metallic	52425ZP	Interstate Black
16113ZP	Yellow Sapphire	50268ZP	LeMans Blue Metallic (Chevy)	52426ZP	Interstate Black
16115ZP	Spruce Green Metallic	50269ZP	Daytona Yellow /Goldenrod Yellow	52428ZP	Boulevard Black
16116ZP	Blue Marlin Metallic	50270ZP	Rallye Green Metallic (Chevy)	52429ZP	Rat Rod Satin Black
21855ZP	Rat Rod Satin Black	50271ZP	Ermine White (Chevy)/Cameo Ivory (Pontiac)	52430ZP	Dead Rat Flat Black
50210ZP	Boulevard Black	50272ZP	Polar White/Can-Am/Classic White	52431ZP	USA Bright White
50211ZP	Chop Top Silver Metallic	50273ZP	Rally Red	52432ZP	Under Hood Black
50212ZP	Pure White				

2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CLASSIFICATION:

FLAMMABLE LIQUIDS:	Category 2
ACUTE TOXICITY Inhalation:	Category 4
ACUTE TOXICITY Oral:	Category 4
ACUTE TOXICITY Dermal:	Category 4
ASPIRATION HAZARD:	Category 1
CARCINOGENICITY:	Category 2
SKIN IRRITATION:	Category 2
EYE IRRITATION:	Category 2A
SPECIFIC TARGET ORGAN TOXICITY:	
SINGLE EXPOSURE:	Category 3 (Respiratory, Central Nervous System)
REPEATED EXPOSURE:	Category 2 (Liver, Kidney, Central Nervous System)

GHS label elements**PICTOGRAMS****SIGNAL WORD: Danger**

HAZARD STATEMENTS: Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin, causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

PREVENTION: Read all warning statements on all labels for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Use personal protective equipment as required, (see Section 8). Wear protective gloves, protective clothing and eye/face protection. Wear an appropriate, properly fitted fresh air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8.

RESPONSE: IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

If medical advice is needed, have product container/label and Safety Data Sheet at hand.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish, do not use water, (see Section 5).

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

DISPOSAL: Dispose of contents and container with an approved waste disposal facility, in compliance with all local, regional, national and international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range % by Wt
ACETONE	67-64-1	15 - 25 %
TITANIUM DIOXIDE	13463-67-7	20 - 35 %
METHYL AMYL KETONE	110-43-0	10 - 20 %
BUTYL ACETATE	123-86-4	5 - 10 %
XYLENE	1330-20-7	5 - 10 %
TERTIARY BUTYL ACETATE	540-88-5	1 - 5 %

4. FIRST AID MEASURES

EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.

SKIN: Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If symptoms persist, seek medical attention. Wash clothing separately and clean shoes before reuse.

INGESTION: Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

INHALATION: Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear. To prevent aspiration, keep head below knees.

NOTES TO PHYSICIAN: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours after exposure.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

FIRE FIGHTING PROCEDURES: Fight as volatile liquid fire. Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: Highly flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS: Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority if spill is in excess of reportable quantity, in compliance with local/regional/national regulations.

PERSONAL PRECAUTIONS: Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

METHOD OF CLEANING UP: For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, and see Section 13.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment.

This material is part of a multiple component system, read the Safety Data Sheet(s) for all components before mixing, as the mixture will have the hazards of all of its parts. Empty containers retain product residue and can be hazardous. Do not reuse container.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES: Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Components	CAS	Exposure Limits
ACETONE	67-64-1	ACGIH TWA 500 PPM OSHA PEL TWA 1,000 PPM
BUTYL ACETATE	123-86-4	ACGIH TWA 150 ppm OSHA PEL TWA 150 ppm
METHYL AMYL KETONE	110-43-0	ACGIH TWA 50 PPM OSHA PEL TWA 100 PPM
TERTIARY BUTYL ACETATE	540-88-5	ACGIH TWA 200 PPM OSHA PEL TWA 200 PPM
TITANIUM DIOXIDE	13463-67-7	ACGIH TLV 10mg/m ³ OSHA PEL TWA 15mg/m ³ dust
XYLENE	1330-20-7	ACGIH TWA 100 PPM OSHA PEL TWA 100 PPM

ENGINEERING CONTROLS: Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

SKIN: Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

RESPIRATORY: Wear an appropriate, properly fitted fresh-air supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted or any time airborne contaminate levels exceed exposure limits. Follow respirator manufacturer's directions and observe OSHA regulations for respirator use (29 cfr 1910.134).

WORK HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Do not breathe vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Liquid in various colors

ODOR: Typical

ODOR THRESHOLD: Not available

pH: Not available

MELTING POINT: Not applicable

BOILING POINT: 133°F

FLASH POINT AND METHOD: -4°F TCC

EVAPORATION RATE: Not available

FLAMMABILITY(Solid/Gas): Not applicable

FLAMMABLE LIMITS: .5 - 13.0

VAPOR PRESSURE: Not available

VAPOR DENSITY: Heavier than air

DENSITY (lbs/gl): 7.7 - 11.0

SPECIFIC GRAVITY: .9 - 1.20

% SOLUBILITY IN WATER: Not available

OCTANOL/WATER PARTITION COEFFICIENT: Not available

AUTO-IGNITION TEMPERATURE: Not available

DECOMPOSITION TEMPERATURE: Not available

VISCOSITY: 54 - 56 Krebs Units

VOC INFORMATION: This is a Low-VOC Automotive Topcoat (Single-Stage). VOC (both Actual and Regulatory) as supplied, varies by color. Please see information on product label for specific VOC contents. When mixed as directed, RTS VOC will not exceed 2.8 lbs./gallon.

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Under normal conditions of storage and use, hazardous polymerization will not occur.

CONDITIONS TO AVOID: Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.

CHEMICAL STABILITY: The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and possible oxides of nitrogen

INCOMPATIBLE MATERIALS: Alkaline materials, strong acids and oxidizing materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of use and storage, hazardous reactions will not occur.

11. TOXICOLOGICAL INFORMATION

This product has not been tested as a whole, individual component data, (where available), is listed below:

ACETONE(67-64-1)

Acute Dermal Toxicity	LD50: >7,426 mg/kg (guinea pig)
Acute Inhalation Toxicity	LC50: 32,000 ppm 4hrs (rat)
Acute Oral Toxicity	LD50: 5,800 mg/kg (rat)
Target Organ, Single Exposure	
Category 3: Respiratory, Central Eye Irritation	Nervous System, May cause respiratory irritation, drowsiness or dizziness. Category 2: Causes eye irritation.

BUTYL ACETATE(123-86-4)

Acute Dermal Toxicity	LD50: >14,112 mg/kg (rabbit)
Acute Oral Toxicity	LD50: 12,789 mg/kg (rat)
Target Organ, Single Exposure	
Category 3: Central Nervous System	May cause drowsiness or dizziness.

METHYL AMYL KETONE(110-43-0)

Acute Inhalation Toxicity LC50: >16.7 mg/l 4hrs Category 4 Harmful if inhaled.
 Acute Oral Toxicity LD50: 1,600 mg/kg (rat) Category 4 Harmful if swallowed.
 Target Organ, Single Exposure
 Category 3: Central Nervous System, May cause drowsiness or dizziness.

TERTIARY BUTYL ACETATE(540-88-5)

Acute Dermal Toxicity LD50: >2,000 mg/kg
 Acute Inhalation Toxicity LC50: 12.52 mg/l 4hrs Category 4 Harmful if inhaled.
 Acute Oral Toxicity LD50: 4,500 mg/kg
 Target Organ, Single Exposure
 Category 3: Respiratory, Central Nervous System, May cause respiratory irritation, drowsiness or dizziness.

TITANIUM DIOXIDE(13463-67-7)

Acute Dermal Toxicity LD50: >5,000 mg/kg (rabbit)
 Acute Inhalation Toxicity LC50: >6.8 mg/l 4hrs (rat)
 Acute Oral Toxicity LD50: >5,000 mg/kg (rat)
 Carcinogenicity Classification IARC Group 2B Suspected of causing cancer.

XYLENE(1330-20-7)

Acute Dermal Toxicity LD50: >4,200 mg/kg (rabbit) Category 4 Harmful in contact with skin.
 Acute Inhalation Toxicity LC50: >20 mg/l 4hrs (rat) Category 4 Harmful if inhaled.
 Acute Oral Toxicity LD50: 3,523 mg/kg (rat)
 Aspiration Toxicity Category 1: May be fatal if swallowed and enters airways.
 Target Organ, Single Exposure
 Category 3: Respiratory, May cause respiratory irritation.
 Target Organ, Repeated Exposure
 Category 2: Liver, Kidney, Central Nervous System, May cause damage to organs through prolonged or repeated exposure.
 Eye Irritation Category 2A: Causes serious eye irritation.
 Skin Irritation Category 2: Causes skin irritation.
 Carcinogenicity Classification Contains Ethyl Benzene: IARC Group 2B Suspected of causing cancer.

ECOLOGICAL INFORMATION

This product has not been tested as a whole, individual component data, (where available), is listed below:

ACETONE(67-64-1)

Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 5,540 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 12,700 mg/l 48hrs
Toxicity to algae	Chlorella pyrenoidosa (algae)	EC50: 3,020 mg/l 14 days
Persistence and degradability	Biodegradability	Readily

BUTYL ACETATE(123-86-4)

Toxicity to fish	Pimephales promelas (flathead minnow)	LC50: 18 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	daphnia magna (Water flea)	LC50: 44 mg/l 48hrs
Toxicity to algae	Desmodesmus subspicatus (green algae)	ErC50: 648 mg/l 72 hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Pow: 3.2

METHYL AMYL KETONE(110-43-0)

Toxicity to fish	Pimephales promelas (flathead minnow)	LC50: 131 mg/l 96hrs
Toxicity to algae	Selenastrum capricornutum (green algae)	ErC50: 98.2 mg/l 72 hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Pow: 1.98

TERTIARY BUTYL ACETATE(540-88-5)

Acute aquatic toxicity	Harmful to aquatic life.	
Toxicity to fish	Low acute toxicity to fish	
Toxicity to daphnia and other aquatic invertebrate	Low acute toxicity to aquatic invertebrates.	
Toxicity to algae	Harmful to algae. Can inhibit growth of aquatic algae	EC50: 16 ml/l 72hrs
Toxicity to bacteria	Pseudokirchneriella subcapitata (green algae)	EC50: 64 mg/l 96hrs
Persistence and degradability	High concentrations may be harmful to sewage treatment plant microbes	1.5 mg/l
Bioaccumulative potential	Biodegradability	Inherently biodegradable
	Bioaccumulation	Not expected to bioaccumulate

XYLENE(1330-20-7)

Acute aquatic toxicity	Expected to be toxic to aquatic organisms.	
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 2.6 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 1 mg/l 24hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	ErC50: 4.36 mg/l 73hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Pow: 3.12 - 3.16

13. DISPOSAL CONSIDERATIONS

RECOMMENDATIONS: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, consult your local or regional authorities.

14. TRANSPORT INFORMATION**UN NUMBER:** UN1263**UN PROPER SHIPPING NAME:** PAINT**TRANSPORT HAZARD CLASS:** 3**PACKING GROUP:** II

SPECIAL PRECAUTIONS: The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

15. REGULATORY INFORMATION**UNITED STATES FEDERAL REGULATIONS:****OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200

A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA RQ - 40 CFR302.4 (a)****List of Hazardous Substances and Reportable Quantities (RQ)**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>RQ</u>
ACETONE	67-64-1	5,000 lbs.
BUTYL ACETATE	123-86-4	5,000 lbs.
TERTIARY BUTYL ACETATE	540-88-5	5,000 lbs.
XYLENE	1330-20-7	100 lbs
Xylene Component: ETHYL BENZENE	100-41-4	1,000 lbs.

SARA Section 311/312 Hazard Category - 40 CFR 370.2

This product is considered, under applicable definitions, to meet the following categories:

(X) Fire Hazard (X) Acute Health Hazard (X) Chronic Health Hazard

SARA 313 Components - 40 CFR 372.65

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

<u>Chemical Name</u>	<u>CAS Number</u>
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

STATE REGULATIONS:**California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
TITANIUM DIOXIDE	13463-67-7
Xylene Component: ETHYL BENZENE	100-41-4

New Jersey, Pennsylvania, Massachusetts Right-To-Know Component Information

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
BUTYL ACETATE	123-86-4
METHYL AMYL KETONE	110-43-0
TERTIARY BUTYL ACETATE	540-88-5
TITANIUM DIOXIDE	13463-67-7
XYLENE	1330-20-7
Xylene Component: ETHYL BENZENE	100-41-4

16. OTHER INFORMATION

HMIS RATING	
Health:	3
Flammability:	3
Personal Hazard:	1
Personal Protection:	J



0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. The Eastwood Company makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

DATE ISSUED: 2/05/2018
Version No.: 50200211-5