



DO THE JOB RIGHT.

## SAFETY DATA SHEET

### SECTION 1 / Identification

**IDENTITY: EASTWOOD PLASTIC BUFFING COMPOUND**  
**PRODUCT CODE: 32035**

**Product Use:** Compound Buffing

**Manufacturer/Distributor:** Eastwood Company  
**Address:** 263 Shoemaker Road Pottstown, PA 19464  
**Telephone No:** 800-343-9353  
**Emergency Telephone No:** 800-424-9300 ChemTrec  
**Date:** 03/11/2015

### SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.  
Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

**Signal Word:**



**Warning**

### SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Hydrogenated Fatty Acid	57-11-4	less than 21 %
Aluminum Oxide	1344-28-1	less than 65 %
Silica	1317-95-9	less than 25 %
Wax	64742-43-4	less than 15 %
Calcium Carbonate	1317-65-3	less than 30 %

## SECTION 4: First Aid Measures

**Ingestion:** If swallowed - seek medical attention

**Inhalation:** Move to a fresh air environment

**Eye Contact:** Flush thoroughly with water and call physician

**Skin Contact:** Remove dust from skin with warm water and soap

## SECTION 5: Firefighting measures

**Flash Point (method used):** 350° F ( CoC )

**LEL:** N/A

**Extinguishing Media:** CO<sub>2</sub> Dry Chemical

**Special Fire Fighting Instructions:** Use Air Pack - Treat as Grease Fire

**Unusual Fire and Explosion Hazard:** Dense smoke

**Flammable Limits:** No Data

**UEL:** N/A

## SECTION 6: Accidental release measures

If material is spilled or released - sweep up with broom and dispose. Follow normal clean up procedures per State and Local laws. Care given to prevent dust from becoming airborne.

## SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in a cool dry area

No other precautions apply

## SECTION 8: Exposure controls/personal protection

Hazardous Guidelines:

Hazardous Component	OSHA PEL	ACGIH / TLV
Hydrogenated Fatty Acid	15 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>
Aluminum Oxide	15 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>
Silica	0.1 mg ./m <sup>3</sup>	0.1 mg ./m <sup>3</sup>
Wax		
Calcium Carbonate	15 mg ./m <sup>3</sup>	10mg ./m <sup>3</sup>

**Special:** None

**Mechanical ( General ):** To maintain employee below permissible limits.

**Respiratory Protection:** OSHA/MOHA approved dust mask / respirator

**Gloves:** Yes

**Eye Protection:** Safety Glasses

**Other:** Long sleeve protective clothing

**SECTION 9: Physical and chemical properties****Boiling Point:** > 450°F**Vapor Pressure (mm Hg):** N/A**Vapor Density:** N/A**Solubility in Water:** Insoluble**Appearance & Odor:** Blue Bar Form**Specific Gravity:** 1.9 to 2.6**Melting Point:** 140°F**Evaporation Rate:** N/A**( Butyl Acetate=1)****SECTION 10: Stability and Reactivity****Stability:** Yes**Incompatibility:** N/A**Hazardous Decomposition of By-Products:** N/A**Hazardous Polymerization:** Will not occur**Conditions to Avoid:** N/A**SECTION 11: Toxicological Information****Route(s) of Entry :**    **Inhalation:** Yes        **Skin:**        No        **Ingestion:** Yes**Health Hazards ( Acute and Chronic):** Coughing and sneezing. Buffing operations may cause lint and abrasives to become airborne. Respirator and ventilation is recommended.**Effects of overexposure:** N/A**Carcinogenicity:** N/A**NTP:** N/A**IARC Monographs:** No**OSHA Regulated:** No**SECTION 12: Ecological information ( Non-Mandatory )****SECTION 13: Disposal considerations ( Non-Mandatory )****SECTION 14: Transport Information ( Non-Mandatory )****SECTION 15: Regulatory Information ( Non-Mandatory )****SECTION 16: Other Information ( Non-Mandatory )****Revision Date:** 03/11/2015**Revision Summary:****Update all sections****Revised By:** A.Battle