

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/17/2009


















Reviewed on 03/17/2009

1 Identification of substance· **Product details**· **Trade name:** 50022Z - Flexible Primer Surfacer Aerosol Gray· **Article number:** 39133· **Distributed by:**The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464

USA & Canada: 800-345-1178

Outside USA: (610) 323-2200

· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300**2 Composition/Data on components**· **Chemical characterization**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened Danger:  2.2/1 Warning:  2.5/C	13 - 30%
67-64-1	acetone Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	13 - 30%
14808-60-7	Quartz (SiO ₂) Danger:  3.6/1B, 3.8/2 Warning:  3.3/2A	13 - 30%
1330-20-7	xylene Danger:  3.1.D/3, 3.1.I/4, 3.2/2 Warning:  2.6/3	10 - 13%
110-19-0	isobutyl acetate Danger:  2.6/2	7 - 10%
	ACRYLIC RESIN Warning:  3.2/2, 3.3/2A, 3.8/3	1.5 - 5%
108-88-3	toluene Danger:  2.6/2;  3.10/1, 3.7/2, 3.9/2 Warning:  3.2/2, 3.8/3	1.5 - 5%
123-86-4	n-butyl acetate Warning:  2.6/3;  3.8/3	1.5 - 5%
78-93-3	butanone Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	1.5 - 5%

3 Hazards identification· **Hazard description:**Toxic
Extremely flammable· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

(Contd. on page 2)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacer Aerosol Gray

(Contd. of page 1)

Warning! Pressurized container.

May cause cancer by inhalation.

Extremely flammable.

Irritating to eyes and skin.

Danger of serious damage to health by prolonged exposure.

Also harmful: possible risk of irreversible effects through inhalation.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

77.4 % by mass of the contents are flammable

Keep out of the reach of children.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



*Health = *2*

Fire = 4

Reactivity = 0

· **GHS label elements**



Danger

2.3/1 - Extremely flammable aerosol.



Danger

3.6/1B - May cause cancer.

3.8/2 - May cause damage to organs.



Warning

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

Warning

3.1/5 - May be harmful in contact with skin.

· **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacer Aerosol Gray

(Contd. of page 2)

Use personal protective equipment as required.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Storage:

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 3)

*Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.**Keep respiratory protective device available.**Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.***· Storage:****· Requirements to be met by storerooms and receptacles:***Store in a cool location.**Observe official regulations on storing packagings with pressurized containers.***· Information about storage in one common storage facility: Store away from oxidizing agents.****· Further information about storage conditions:***Keep receptacle tightly sealed.**Do not gas tight seal receptacle.**Store in cool, dry conditions in well sealed receptacles.**Protect from heat and direct sunlight.***8 Exposure controls and personal protection****· Additional information about design of technical systems: No further data; see item 7.****· Components with limit values that require monitoring at the workplace:****67-64-1 acetone**PEL 2400 mg/m³, 1000 ppmREL 590 mg/m³, 250 ppmTLV Short-term value: 1782 mg/m³, 750 ppmLong-term value: 1188 mg/m³, 500 ppm

BEI

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing

REL 0.05* mg/m³

*respirable dust

TLV 0.025* mg/m³

*as respirable fraction

1330-20-7 xylenePEL 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLV Short-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppm

BEI

110-19-0 isobutyl acetatePEL 700 mg/m³, 150 ppmREL 700 mg/m³, 150 ppmTLV 713 mg/m³, 150 ppm

(Contd. on page 5)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 4)

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	75 mg/m ³ , 20 ppm

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

78-93-3 butanone

PEL	590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	< -17°C (< 1°F)

· **Flash point:** < -17°C (< 1°F)· **Ignition temperature:** 405°C (761°F)· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 233 hPa (175 mm Hg)· **Density at 20°C (68°F):** 0.83 g/cm³· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Solvent content:**

Organic solvents:	77.4 %
VOC content:	57.4 %
	475.7 g/l / 3.97 lb/gal

· **Solids content:** 22.6 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Dangerous reactions** No dangerous reactions known.· **Dangerous products of decomposition:**

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

USA

(Contd. on page 7)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 6)

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic if inhaled.

12 Ecological information

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



· **Hazard class:**

2.1

· **Identification number:**

UN1950

· **Packing group:**

-

(Contd. on page 8)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 7)

- **Proper shipping name (technical name):** AEROSOLS, flammable
- **Label** 2.1

- **Land transport TDG (Canada) and ADR/RID (Europe):**



- **Hazard class:** 2 - 5F Gases
- **UN-Number:** 1950
- **Packaging group:** -
- **Label:** 2.1
- **Description of goods:** 1950 AEROSOLS

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Propper shipping name:** AEROSOLS

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Propper shipping name:** AEROSOLS, flammable

- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulations

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

ACRYLIC RESIN

108-88-3 toluene

(Contd. on page 9)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 8)

78-93-3	butanone
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
100-41-4	ethylbenzene
67-56-1	methanol

· TSCA (Toxic Substances Control Act):

68476-86-8	Petroleum gases, liquefied, sweetened
67-64-1	acetone
14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
110-19-0	isobutyl acetate
108-88-3	toluene
123-86-4	n-butyl acetate
13463-67-7	titanium dioxide
78-93-3	butanone
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
7631-86-9	silicon dioxide, chemically prepared
21645-51-2	aluminium hydroxide
51274-00-1	YELLOW IRON OXIDE

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
1330-20-7	xylene	I
108-88-3	toluene	II
78-93-3	butanone	I
111-76-2	2-butoxyethanol	CBD
100-41-4	ethylbenzene	D

(Contd. on page 10)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacer Aerosol Gray

(Contd. of page 9)

· IARC (International Agency for Research on Cancer)		
14808-60-7	Quartz (SiO ₂)	I
1330-20-7	xylene	3
108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
· TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
14808-60-7	Quartz (SiO ₂)	A2
1330-20-7	xylene	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	
67-56-1	methanol	
· OSHA-Ca (Occupational Safety & Health Administration)		
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Toxic

Extremely flammable

· Hazard-determining components of labelling:Quartz (SiO₂)**· Risk phrases:**

May cause cancer by inhalation.

Extremely flammable.

Irritating to eyes and skin.

Danger of serious damage to health by prolonged exposure.

Also harmful: possible risk of irreversible effects through inhalation.

(Contd. on page 11)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 03/17/2009

Reviewed on 03/17/2009

Trade name: 50022Z - Flexible Primer Surfacers Aerosol Gray

(Contd. of page 10)

· Safety phrases:*Avoid exposure - obtain special instructions before use.**Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).**In case of insufficient ventilation, wear suitable respiratory equipment.**In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).***· Special labeling of certain preparations:***Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.**77.4 % by mass of the contents are flammable**Keep out of the reach of children.***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.**· Contact:** Steve Gaver**· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)**ICAO: International Civil Aviation Organization**ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ACGIH: American Conference of Governmental Industrial Hygienists**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*

USA