

SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



Date Prepared : 07/22/2015

SDS No : 51653Z Part A_ENG

Date Revised : 05/13/2016

Revision No : 2

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A
Product Description : Part A Epoxy Seam Sealer, 125 ml / 4.23 fl oz US
General Use : Epoxy adhesive / sealant
Product Stock/Code : 51653 Z (Kit: 250 ml / 8.45 fl oz US)
Chemical Family : Epoxy / époxy
Molecular Formula : Mixture / Mélange

Manufacturer / Supplier

The Easthill Group
Dba The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464
USA & Canada: 800-343-9353
Outside USA: (610) 323-2200
www.eastwood.com

Emergency Telephone Numbers (24 hour)

CHEMTREC : (800) 424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

Health hazards:

Skin Irritation, Category 2
Eye Irritation, Category 2A
Skin Sensitizer, Category 1
Reproductive Toxicity, Category 1B

Label elements

Hazardous components for labelling:

Epoxy resin and Benzyl butyl phthalate



Exclamation
mark



Health
hazard

Signal Word: DANGER

Hazard statement(s)

H315: Causes skin irritation.
H319: Causes serious eye irritation.

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

H317: May cause an allergic skin reaction.

H360: May damage the unborn child. Suspected of damaging fertility.

Precautionary statement(s)

Prevention:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P264: Wash hands thoroughly after handling.

P261: Avoid breathing vapours.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves and eye protection.

Response:

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

Emergency Overview

Immediate concerns: Causes serious eye irritation. Causes skin irritation. May cause sensitization by skin contact. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. May damage the unborn child. Suspected of damaging fertility.

Hazards Not Otherwise Classified:

No data available.

Comments: See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS number
Bisphenol A / epichlorohydrin epoxy resin	39 - 41	25085-99-8 (25068-38-6)
Bisphenol A / epichlorohydrin polymer, epoxy terminated	39 - 41	25036-25-3
Benzyl butyl phthalate	19 - 21	85-68-7

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

classified and contribute to the classification of the product and hence require reporting in this section.

4. FIRST AID MEASURES

Eye Contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention, if irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Inhalation: Not expected to present a significant inhalation hazard under anticipated conditions of normal use. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area.

Signs and Symptoms of Overexposure

Eye Contact: Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Skin Contact: Causes skin irritation. Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Ingestion: Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

Inhalation: At room temperature, exposure to vapor is minimal due to low volatility.

Additional Information: No data available.

5. FIRE FIGHTING MEASURES

Flammable Properties: Will burn if involved in a fire.

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material. Use an extinguishing agent suitable for the surrounding fire.

Hazardous Combustion Products: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire Fighting Procedures: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Sensitivity to Static Discharge: Product is not sensitive to static discharge.

Sensitivity to Mechanical Impact: Product is not sensitive to mechanical impact.

6. ACCIDENTAL RELEASE MEASURES

Small Spill: Ensure adequate ventilation. Cover spill area with suitable absorbent material (e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly. Avoid contact with eyes, skin, and clothing.

Environmental Precautions

Water Spill: Do not flush to sewer.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Special Protective Equipment: Clean up spills immediately, observing precautions in Protective Equipment section 8.

7. HANDLING AND STORAGE

General Procedures: Ensure thorough ventilation of stores and work areas.

Handling: Do not use in the presence of open flame or spark. Wear recommended personal protective equipment. Avoid contact with eyes, skin, and clothing. After handling, always wash hands thoroughly with soap and water.

Storage: Store away from heat, sparks, open flames, strong oxidizing agents and direct sunlight. Protect from physical damage. Keep containers tightly closed, when not in use. Store in a cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

OSHA / WHMIS 2015 HAZARDOUS COMPONENTS				
Chemical Name	Occupational Exposure Limits			
	Type	ppm	mg/m ³	
Bisphenol A / epichlorohydrin epoxy resin	USA OEL	-	-- [1]	-- [1]
Bisphenol A / epichlorohydrin polymer, epoxy terminated	USA OEL	-	-- [1]	-- [1]
Benzyl butyl phthalate	USA OEL	-	[1]	[1]
	EU OEL	TWA	-- [2]	3 [2]
STEL		-- [2]	5 [2]	

Footnotes:

1. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.
2. Austria, Denmark, Sweden

Engineering Controls: Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

Eyes and Face: Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

Skin Contact: Wear chemical resistant gloves.

Respiratory: Generally not required. Wear respiratory protection if ventilation is inadequate.

Protective Clothing: Wear protective clothing as necessary to prevent contact.

Work Hygienic Practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical State** : Liquid
- Odor** : Mild
- Odor Threshold** : No data available.
- Appearance** : Viscous liquid
- Color** : Light blue
- pH** : No data available.
- % Volatiles** : < 0.6% w/w
- Flash Point and Method** : > 200 °C Closed Cup

Flammable Limits : No data available.
Autoignition Temperature : No data available.
Vapor Pressure : No data available.
Vapor Density : No data available.
Boiling Point : No data available.
Freezing Point : No data available.
Melting Point : Not Applicable
Solubility in Water : Practically insoluble
Evaporation Rate (n-butyl acetate = 1) : No data available.
Density : 1.14±0.02g/ml at 20°C
Viscosity : 8000 to 15000 cps at 25°C
VOC Content : < 7.0 g/l (< 0.6% w/w)
Oxidizing Properties : None

Comments:

VOC Compliance Statement

Part A VOC Content: Less Exempts: < 7 g/l (< 0.058 lb/gal)
Total Material: < 7 g/l (< 0.058 lb/gal)
Part A Density: 1.14 ± 0.02 g/ml
Part A Total Volatiles: < 0.6 % w/w
Part A Exempt Content: 0 % w/w; 0% v/v

VOC Regulation: CARB-California, OTC state, Canada proposed Consumer Product Regulations
Coating Category: Sealant or Caulking Compound, Chemically Curing, non-aerosol
Mixed Kit VOC Content: < 0.4 % w/w
Less Exempts: < 5.0 g/l (< 0.04 lb/gal)
Total Material: < 5.0 g/l (< 0.04 lb/gal)

The product VOC content meets the current 3% w/w limit under the CARB Consumer Product Regulations for Sealant or Caulking Compound, Chemically Curing, non-aerosol. 50 State compliant.

Note: In California this product is exempt under Adhesives and Sealants district rules (meets small container exemption - packaged in ≤ 475 ml (16 fl oz) cartridges) but is covered by the CARB Consumer Product Regulation.

10. STABILITY AND REACTIVITY

Reactive Hazard : No

Hazardous Polymerization: Not expected to occur.

Stability: Stable.

Conditions to Avoid: Keep away from flames and incompatible materials. Keep away from flames and any object that sparks.

Possibility of Hazardous Reactions: No data available.

Hazardous Decomposition Products: Carbon Monoxide and other toxic vapors.

Incompatible Materials: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Chemical Name	Oral LD ₅₀ mg/kg (rat)	Dermal LD ₅₀ mg/kg (rabbit)	Inhalation LC ₅₀ mg/l
Bisphenol A / epichlorohydrin epoxy resin	11,400 > 15,000	> 22,800	No data available.
Bisphenol A / epichlorohydrin polymer, epoxy terminated	> 15,000	23,000	No data available.
Benzyl butyl phthalate	2330	> 10,000	No data available.

Acute Toxicity - Dermal LD₅₀: Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute Toxicity - Oral LD₅₀: Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

Acute Toxicity - Inhalation LC₅₀: The mixture is not classified due to lack of data. At room temperature, exposure to vapor is minimal due to low volatility. An estimate based on component information. Not classified.

Notes: < 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

Skin Irritation / Corrosion: Contains: Epoxy resin. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash.

Eye Irritation / Serious Eye Damage: Contains: Epoxy resin. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Respiratory / Skin Sensitizer: Contains: Epoxy resin. May cause sensitization by skin contact. The mixture is classified as: Skin Sensitizer, category 1 based on ingredient data (≥ 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A or ≥ 1.0% ingredients classified as a skin sensitizer, sub-category 1B). Prolonged contact with this product can cause reddening, swelling, rash scaling or blistering. In those who have developed skin sensitization, these symptoms can develop as a result of contact with very small amount of the liquid material.

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

Germ Cell Mutagenicity: Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

Carcinogenicity

Chemical Name	NTP status	IARC status	OSHA status	Other
Bisphenol A / epichlorohydrin epoxy resin	--	--	--	--
Bisphenol A / epichlorohydrin polymer, epoxy terminated	--	--	--	--
Benzyl butyl phthalate	--	3	--	--

Notes: Based on available data, the classification criteria for Carcinogenicity are not met for this mixture (<

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

0.1% ingredients classified as a Carcinogen, category 1 or 2).

Reproductive Toxicity: Contains: Benzyl butyl phthalate. May cause adverse reproductive effects. May damage the unborn child. Suspected of damaging fertility. The mixture is classified as: Reproductive Toxicity, category 1 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as Reproductive Toxicity, category 1A or 1B).

Specific Target Organ Toxicity - Single Exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Single Exposure are not met for this mixture ($< 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 1 or 2 and $< 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3).

Specific Target Organ Toxicity - Repeated Exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Repeated Exposure are not met for this mixture ($< 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 1 or 2). Prolonged skin contact may cause reddening, swelling, rash, scaling, blistering, and in some cases, skin sensitization.

Aspiration Hazard: Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ($< 10\%$ ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity $> 20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$).

12. ECOLOGICAL INFORMATION

Environmental Data: No data available.

Ecotoxicological Information: No data available.

Bioaccumulation/Accumulation: No data available.

Distribution: No data available.

Aquatic Toxicity (Acute): No data available.

Chemical Fate Information: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

Product Disposal: Empty containers retain product residue; observe all precautions for product. Decontaminate containers prior to disposal.

14. TRANSPORT INFORMATION

DOT (Department of Transportation)

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name : Benzyl Butyl Phthalate and Epoxy Resin

Primary Hazard Class/Division: 9

UN/NA Number : 3082

Packing Group : III

Marine Pollutant : Yes

Other Shipping Information:

These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

Air (ICAO/IATA)

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical Name : Benzyl Butyl Phthalate and Epoxy Resin
UN/NA Number : 3082
Primary Hazard Class/Division: 3
Packing Group : III

Vessel (IMO/IMDG)

Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical Name : Benzyl Butyl Phthalate and Epoxy Resin
UN/NA Number : 3082
Primary Hazard Class/Division: 3
Packing Group : III
Marine Pollutant : Yes
Label : None

Note: With an inner packaging < 5.0 L, this product may be shipped as a Limited Quantity.

Canadian Transportation of Dangerous Goods Regulations

Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Technical Name : Benzyl Butyl Phthalate and Epoxy Resin
UN/NA Number : 3082
Primary Hazard Class/Division: 3
Packing Group : III
Label : None

TDG Note:

These Regulations do not apply to the handling, offering for transport or transporting of less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle.

15. REGULATORY INFORMATION

UNITED STATES

SARA Section 311/312 Hazard Categories

Fire Hazard : No
Sudden Release of Pressure : No
Reactive Hazard : No
Product Acute Toxicity : Yes
Product Chronic Toxicity : Yes

EPCRA Section 313 Toxic Chemicals

Chemical Name	Wt.%	CAS number
Benzyl butyl phthalate	19 - 21	85-68-7

EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status:

This product contains no listed extremely hazardous substances that are subject to the reporting

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical Name	Wt.%	RQ
Benzyl butyl phthalate	19 - 21	100

TSCA (The Toxic Substances Control Act)

TSCA Status:

All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) - Hazardous Air Pollutants

CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(b) or CAA 112(r).

California Proposition 65

Chemical Name	Wt.%	Listed
Benzyl butyl phthalate	19 - 21	Developmental Toxicity

OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

Name	CAS No.	NPRI Part No.
Benzyl butyl phthalate	85-68-7	1A (VOC)

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments VOC Content -- See section 9.

16. OTHER INFORMATION

Reason for Issue: NEW

Prepared By : Regulatory Compliance / Conformité

Date Revised: 05/13/2016

réglementaire **Information Contact:** 800-343-9353


Eastwood 2K Self Leveling Seam Sealer 51653 Z Part A

Revision Summary: This MSDS replaces the 07/22/2015 MSDS. Revised: **Section 2:** Emergency Overview - Immediate concerns. **Section 9:** Density

HMIS RATING

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



NFPA 30 / 30B Storage Classification: Combustible Liquid IIIB

Manufacturer Supplemental Notes: None

Data Sources: Not Available

Additional SDS Information:

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

General Statements: No data available.

Comments: None

Manufacturer Disclaimer: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.