

Plastic Magic Adhesion Promoter

Surface modifier

1050 Series

Plastic Magic works like magic in preventing paint peeling on new, unfinished plastic parts and previously painted surfaces even without sanding. There is no need to identify the type of plastic. Plastic Magic works on TPO and all other problem plastics to make primers and paints stick to any kind of automotive plastic, inside or outside the vehicle.

Benefits:

- Prevents paint peeling on new, unfinished plastic parts and previously painted surfaces.
- No need to identify plastic. Plastic Magic works on all plastics.
- Easy to use. Just spray on and allow to flash off.
- Plastic Magic can be top coated with any type paint system.

Application:

- Clean first with soap and water to remove water soluble contaminants.
- Clean with Super Clean plastic cleaner (Part number 1000) to remove mold release agents and other contaminants.
- Apply a medium-wet coat of Plastic Magic and allow to flash off at least 2-3 minutes, then follow with a full-wet coat and allow to dry at least 15 minutes before color coating.
- Gallon and quart sizes may be poured into a spray bottle, into a spray gun, or poured straight from the container. Aerosol can is ready to use.



Product Specifications

Size	Part Number	Shipping Weight	Dimensions
Gallon F-Style (3.785 liters)	1050-1	7.15 lb (3.2 kg)	6.5 in. width x 4.1 in. depth x 10.3 in. height (16.5cm x 10.4cm x 26.2cm)
Quart F-Style (946 ml)	1050-4	2.06 lb (0.93 kg)	4.5 in. width x 2.5 in. depth x 7.4 in. height (11.7cm x 6.1cm x 18.8)
Aerosol 19 fl. oz. (562 ml)	1050-A	1.20 lb (0.54 kg)	9.5 in. height x 2.7 in. diameter (24 cm x 7 cm)



Customer Support:
Toll Free: 800-633-3047
Phone: 256-638-4103
www.polyvance.com

