

**PRODUCT:** MAXIM™ FAST URETHANE ADHESIVE

**PART NUMBER:** 100887      250mL Cartridge      6 units/case

**DESCRIPTION:** Maxim™ Fast Urethane Adhesive is a two-component urethane repair material that provides incredible strength and sandability. This urethane material is used for non-structural repairs on fiberglass, SMC, PUR, RIM, RRIM, PP, TPO, TPE, EPDM and other automotive plastics.

**FEATURES & BENEFITS:**  
Easy to use: excellent gun ability and sandability  
Fast setting, excellent for two-sided repairs  
Cure time can be accelerated with heat

**PREPARATION:** Wash the repair area with soap and warm water. Thoroughly dry entire repair area (i.e. compressed air, heat, etc.). Use an All-Purpose Cleaning Solvent on a clean, lint-free cloth and wipe the repair area (Wipe from the center of the repair area to the outside). Use a clean, dry cloth to wipe the area dry. Sand and taper the repair area according to recommendations. Apply Adhesion Promoter according to recommendations.

**APPLICATION:** Apply Fast Urethane adhesive to the repair area. Allow to dry, then sand.

Apply primer surface according to paint manufacturer's recommendations.

<b>TECHNICAL SPECIFICATIONS:</b>	▪ Appearance	Black / Opaque
	▪ VOC	Refer to Section 9 of the Safety Data Sheet
	▪ Working Time	1-3 minutes
	▪ Sanding Time	20-30 minutes
	▪ Full Cure / Paint Time	1 hours

**NOTE:** Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

**SAFETY & HANDLING:**  
For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place.

Safety Data Sheets can be found online at [evercoat.com](http://evercoat.com).